

GENERAL INFORMATION

SOVEREIGN|RE

STANDARDS	ISO/DIS 19322.2:2016 EN649	Heterogeneous PVC
SIZE		1520 x 228 mm
THICKNESS	ISO 24346	6,5 mm
WEAR LAYER	ISO 24340	0,70 mm
INSTALLATION SYSTEM		Click i4F
ACOUSTIC PAD		1,5 mm 10*IXPE
BEVEL		Large Painted Bevel
EMBOSSING		EIR Embossing
GLOSS LEVEL		2-4 degrees
QUANTITY		7 planks / box 44 boxes / pallet
COVER AREA		2,43 m ² / box 106,45 m ² / pallet

PERFORMANCE

INFLAMMABILITY	EN1350-1 EN ISO 9239-1 EN ISO 11925-2	B _{fl} -s1
STAINING RESISTANCE	EN ISO 26987:2012	Class 0
COLOUR FASTNESS	EN ISO 105-B02	Grade 6
FUNGI RESISTANCE	ISO 846	Growth intensity 0
DIMENSIONAL STABILITY	ISO 23999	≤ 0,15 %
ACOUSTIC INSULATION	EN ISO 10140-3 ISO 717-2	Δ Lw 22DB
RESIDUAL INDENTATION	EN 433	< 0,1 mm
CASTOR CHAIR	ISO 4918 EN 425:2002	Pass
FORMALDEHYDE EMISSION	EN 14041:2004	Class E1
SLIP RESISTANCE	EN 13893 DN 51130	DS R10
ELECTROSTATIC BEHAVIOR	EN 1815	Pass
REACH	EC N° 1907/2006	Pass
VOC EMISSION	FRENCH VOC REGULATION	A+
UNDERFLOOR HEATING		Yes, 27°C max.

CLASSIFICATION & GUARANTEE

CLASSIFICATION	ISO 10874 Light commercial ISO 10874 Domestic EN 685 Light commercial EN 685 Domestic	Class 34 
GUARANTEE	Domestic Light commercial Commercial	25 years 20 years 15 years

